



### AVAILABLE MOUNTING CONFIGURATIONS


2STH-F FRAME MOUNT  
2STH-EM ENGINE MOUNT

### OPERATING LEVELS

<b>MIN FLOW</b>	50 GPM	11.5 m <sup>3</sup> /h
<b>MAX FLOW</b>	490 GPM	112.7 m <sup>3</sup> /h
<b>DISCHARGE SIZE</b>	2"	50 mm
<b>SUCTION SIZE</b>	3"	75 mm
<b>SOLIDS HANDLING</b>	1.5"	3.8 mm
<b>MAX SPEED</b>	2950 RPM	2950 RPM
<b>SHUT-OFF HEAD</b>	188'	57.3 m
<b>BEP HEAD</b>	132'	40.2 m
<b>BEP FLOW</b>	320 GPM	73.6 m <sup>3</sup> /h
<b>BEP PERCENT</b>	49%	49%

<b>PARTS</b>	<b>STANDARD MATERIAL (ALL IRON)</b>
<b>VOLUTE CASING</b>	DUCTILE IRON, ASTM A536, 65-45-12
<b>IMPELLER</b>	DUCTILE IRON, ASTM A536, 100-70-03
<b>IMPELLER SCREW</b>	304 STAINLESS STEEL
<b>BACKPLATE/BACKET</b>	DUCTILE IRON, ASTM A536, 65-45-12
<b>WEAR PLATE</b>	MILD STEEL
<b>BEARING FRAME</b>	DUCTILE IRON, ASTM A536
<b>SHAFT</b>	17-4 PH STAINLESS STEEL
<b>SHAFT SLEEVE</b>	304 STAINLESS STEEL
<b>FASTENERS</b>	GRADE 5 STEEL
<b>MECHANICAL SEAL</b>	SILICON CARBIDE vs. SILICON CARBIDE, TYPE 2

- FIVE-YEAR warranty •
- Optional self-cleaning wear plate •
- Modular bearing frame •
- KamalBlower's Cycloseal® with type 2 seal •
- Dual protection of bearings with external seal leakage monitor (vent to atmosphere)
- High Heads up to 180'



A typical picture of the pump is shown. Please contact Cornell Pump Company for further details. All information is approximate and for general guidance only.

### HIGH-HEAD SELF-PRIMER

KamalBlower's self-priming pump, with industry- leading efficiency, runs several efficiency points higher than other manufacturers. Features patented Cycloseal® system and uniquely designed volute for best performance, with a 3" suction and 2" discharge.

- High-efficiency design
- Oversized oil reservoir for better cooling
- Replaceable shaft sleeve
- Heavy-duty ductile iron construction
- Designed for SAE conversion
- High RPM Capability



AGRICULTURE



FOOD



INDUSTRIAL



MINING



MUNICIPAL



OIL &amp; GAS



REFRIGERATION



RENTAL

